

20/34.5 kV, 150 kV BIL, Type C Loadbreak Porcelain Cutout / Arrester Combination w/100A 12kAIC fuseholder

By CHANCE Utility Catalog # C73EN313EX

20/33.5 kV, 150 kV BIL, Loadbreak Type C Porcelain Cutout / Arrester Combination with a 100A, 12kAIC fuseholder, small eyebolt connector and an extended NEMA "B" crossarm bracket.

Features

- Fully Compliant with ANSI/IEEE C37.41 & C37.42 2016
- Interchangeable with ABB Type ICX & S&C(MPS) Type XS
- Single Vent Solid Cap Design
- Uses Universal Style Fuse Links
- Synthetic Arc Quenching Fuse Holder Liner Material
- Ohio Brass Distribution Class Arresters in Standard, Heavy and Riser Pole Duty Ratings
- Non Interchangeable Mounting Assembly

General

Bracket Type	Extended NEMA "B" for
	crossarm
Description - Replacement Fuse Holder	Т730-313Т
Туре	Cutout



*Representative Image

Electrical Ratings

BIL	150 kV
Creep and Leakage Distance	17.3" (440mm)
Current Rating	100 A
Fuselink Current Range	1A to 100A - removable buttonhead fuse link only
Reference Voltage Limit - Minimum	No Restrictions thru 14.4kV; *20.8 thru 34.5kV
Temperature Rise - Max. at 300A	40° C
Voltage - Radio Interference	51.8 micro-volts @ 22kV
Voltage Rating	20/33.5 kV
Logistics	
Standard Package	1
Product Assets	
Catalogs - Type C-Porcelain Cutouts (10A)	

Catalogs - Type C-Porcelain Cutouts (10A) Literature - Switching Line Card_FAQ_2019 Technical Solutions - CH-C73EN313EX-SPEC-EN Video - Hubbell Power Systems Cutout Seminar, Part 2: Experience (VI10004E) Video - Hubbell Power Systems Cutout Seminar, Part 3: Quality (VI10005E)

