

Fiberglass Crossarm, 25 Deadend, 144" (12'), 4-Wire, 5/8" Bracket, with Dual Sided Eyenuts

By Chance Catalog # CDA25G144D4008B

Hubbell Fiberglass Deadend Crossarms are designed to support the conductor when deadending a line or when extra strength is needed, for example, an area with corners or angles or when there are longer spans between poles. Hubbell Fiberglass Crossarms help harden the grid by offering superior fire resistance, longevity, and strength. Hubbell Fiberglass Crossarms are filled with closed cell foam and drilled to your specifications. See part numbering system on drawing for standard drill patterns. We can also accomodate custom drill requests. All Hubbell Fiberglass Crossarms feature a brace-less center mount design with keyhole feature for easy installation. Mounting brackets are made of galvanized steel with 5/8" or 3/4" holes. Deadend brackets include two integrated guy attachments for 7/8" guying hardware. Ultimate guy load is 30K per attachment.

Features

- Sleeves are installed in All drill holes for hardware torque protection Recommended hardware torque: 250 in-lbs.
- Mounting bracket for 5/8" hardware
- · Painted gray with UV inhibitor paint
- Drill Pattern: 008: HPS Standard 144" Deadend

General

Catalog Number CDA25G144D4008B

Material Fiberglass
Strength Rating - Minimum 4,500 lb. lb

Ultimate, Longitudinal (L)

Type Arm

UPC 096359833215

Dimensions

Dimensions 144 in x 4-5/8 in x 3.625 in

Height 3.625 in

Certifications And Compliance

Buy America(n) Qualified Contact Manufacturer

144 in

4-5/8 in

Logistics

Length

Width

Pallet Quantity 25

Product Assets

Brochures - Fiberglass Crossarms

Catalog Page - FIBERGLASS CONSTRUCTION PRODUCTS
Catalogs - CHANCE® Fiberglass Construction Products
Interactive Catalog - Fiberglass Construction Products (12)
Literature - The support you need from the name you trust
Literature - Fiberglass Crossarms Technical & Application
Questions

Sales Drawings - SACDX25

Specifications - CDA25G144D4008B

