CHANCE®

15 kV, 110 kV BIL, Type C Standard Polymer Cutout w/200A 12kAIC fuseholder

By Chance
Catalog # CP710143PXM

15 kV, 110 kV BIL, Standard Type C Polymer Cutout with a 200A, 12kAIC fuseholder, parallel-groove connector and an extended NEMA "B" crossarm bracket.

Features

- Fully Compliant with ANSI/IEEE C37.41 & C37.42 – 2016
- Interchangeable with ABB Type ICX & S&C(MPS) Type XS
- Single Vent Solid Cap Design
- Uses Universal Style Fuse Links
- Synthetic Arc Quenching Fuse Holder Liner Material
- ESP (Enhanced Silicone Polymer) Insulating Material
- TDG (Thermal Diffusion Galvanization) Insulator Assembly Castings

General

Bracket Type	Extended NEMA "B" for crossarm
Catalog Number	CP710143PXM
Description - Replacement Fuse Holder	T710-143TM
Type	Cutout
UPC	096359600527

Electrical Ratings

BIL	110 kV
Creep and Leakage Distance	12.6" (319mm)
Current Rating	200 A
Fuselink Current Range	140A to 200A - removable buttonhead fuse link only
Reference Voltage Limit - Minimum	Thru 14.4kV
Temperature Rise - Max. at 300A	38° C
Voltage - Maximum	15 kV
Voltage - Radio Interference	Ambient @ 9.41kV
Voltage Rating	15 kV

Logistics

Pallet Quantity	63 EA
Standard Package	1

Product Assets

Catalogs - Type C-Polymer Cutouts
Installation Manuals - Standard Cutout Installation Instructions
Literature - Switching Line Card_FAQ_2019
Literature - HUBBELL® | CHANCE® RUS CUTOUT LISTING
Sales Drawings - 110KV BIL Polymer Cutout
Specifications - CP710143PXM
Video - Hubbell Power Systems Cutout Seminar, Part 3: Quality
Video - Hubbell Power Systems Cutout Seminar, Part 2: Experience

©2024 Hubbell Incorporated. All rights reserved