CHANCE®

15/27 kV, 125 kV BIL, Type C Loadbreak Polymer Cutout w/300A Solid Blade

By Chance
Catalog # CP730233P

15/27 kV, 125 kV BIL, Loadbreak Type C Polymer Cutout with a 300A solid blade, parallel-groove connector and no bracket.

Features

- Fully Compliant with ANSI/IEEE C37.41 & C37.42 – 2016
- Single Vent Solid Cap Design
- Uses Universal Style Fuse Links
- Synthetic Arc Quenching Fuse Holder Liner Material
- ESP (Enhanced Silicone Polymer) Insulating Material
- TDG (Thermal Diffusion Galvanization) Insulator Assembly Castings
- Non Interchangeable Mounting Assembly

General

Bracket Type	No Bracket
Catalog Number	CP730233P
Description - Replacement Fuse Holder	T730-233T
Type	Cutout
UPC	096359007012

Electrical Ratings

BIL	125 kV
Creep and Leakage Distance	17.1" (434mm)
Current Rating	300 A
Reference Voltage Limit - Minimum	No Restrictions thru 14.9kV; *20.8 thru 24.9kV
Temperature Rise - Max. at 300A	40° C
Voltage - Radio Interference	36.2 micro-volts @ 15.66kV
Voltage Rating	15/27 kV
Withstand Current - Short Time (10 cycles)	12,000 Amps Asym.

Logistics

Pallet Quantity	24
Standard Package	1

Product Assets

Catalogs - Type C-Polymer Cutouts
Installation Manuals - Load Break Cutout Installation Instructions
Literature - Switching Line Card_FAQ_2019
Literature - HUBBELL® | CHANCE® RUS CUTOUT LISTING
Sales Drawings - Cutout, LDBK 15/27 KV 125 BIL Polymer (CP730-2)
Specifications - CP730233P
Video - Hubbell Power Systems Cutout Seminar, Part 3: Quality
Video - Hubbell Power Systems Cutout Seminar, Part 2: Experience

©2024 Hubbell Incorporated. All rights reserved