



SPOOL INSULATOR DEADEND SECONDARY CLEVIS, w/GRAY ANSI 53-2 INSULATOR

By CHANCE Utility
Catalog # [DC5C36](#)

Clevis bracket for spool insulators used in secondary deadend applications. Minimum ultimate deadend strength is 4,000 lbs. Used with ANSI Class 53-2 and 53-3 spool insulators. Replacement components: clevis pin - 450033P; cotter pin - 056747P.



*Representative Image

Features

- 1-1/2" x 1/2" x 1/8" channel material
- 11/16" x 7/8" dia. mounting hole 5/8" dia. clevis pin with self-locking cotter pin
- Hot dip galvanized per ASTM A-153

General

Coating	Galvanized, ASTM A-154
Material	Steel
Type	Insulated Secondary Clevis
UPC	096359369363

Dimensions

Distance From Pole	N/A
Height	4.50 in
Length	5.00 in
Weight	2.99 lb

Logistics

Pallet Quantity	600
-----------------	-----

Product Assets

[Catalogs - Pole Line Hardware Supplements \(5-53Supp1-19\)](#)
[Sales Drawings - Clevis, Dead End \(SADC5C36\)](#)



A proud member of the Hubbell Family.

©2023 Hubbell Incorporated. All rights reserved.
CH-DC5C36-SPEC-EN | REV 4/2023