

15.5 kV, 110 kV BIL, 600 A, Porcelain (2 1/4" Bolt Circle) insulation, M3 Switch

By CHANCE Utility Catalog # M3D62AR

14.4kV, 110kV, 600 A, Single-Phase Hookstick Disconnect Switch.



*Representative Image

Features

- Fully Compliant with ANSI/IEEE C37.30.1
- 15, 27 & 38kV Voltage Classes
- 110, 125, 150, 200kV BIL Insulation Levels
- 600A & 900A Current Ratings
- Porcelain and ESP Polymer Insulator Assemblies with 2.25" **Bolt Circles**
- · Distribution Base, Serrated Slots
- · Load Break Option Available

General

Distribution Base, Serrated Base Type

Slots

Blade Type Solid Copper (two blade

truss-member)

Cantilever Bending Strength -1,200 Lbs (5.34 kN)

Routine

Color - Insulator Skv Grav Contact Silver

Insulator Type Porcelain (2 1/4" Bolt Circle)

Material - Base Galvanized Steel per ASTM

A153

Tension Range 5000 lb

3,000 in Lbs (339 N-M) Torsional Strength

UPC 096359725022

Dimensions

Bolt Length 10.00 in Weight 38.71 lb

Electrical Ratings

Arc Distance - Dry 6" (152.4mm)

BII 110 kV

Creep and Leakage Distance 10.5" (266.7mm) 1080 A

Current Overload - 8hr

Emergency

Current Rating 600 A Dead-Ending Rating -8,000 Lbs

Working Load

Reference Voltage Limit -14.4kV

Minimum

Temperature Rise - Max. at 28°C

600A

15.5 kV Voltage - Maximum

Withstand Current - Short

Time (10 cycles)

Withstand Current - Short 25kA, symmetrical

Time (2 sec)

Withstand Current - Short 16kA, symmetrical

Time (3 sec)

Certifications and Compliance

Industry Standard(s) All Applicable ANSI/IEEE

Standards

40kA, asymmetrical

Logistics

Pallet Quantity 42 EA Standard Package

Product Assets

Catalogs - Hookstick Operated Switches (CA10230E 14B) Installation Manuals - Instructions for CHANCE Type M3

Distribution Switch (P807-0198)

Installation Manuals - Type M3C Single Insulator Disconnect Switch for Distribution Switching (PSP8070357)

Installation Manuals - M3_Instructions

Literature - SA-M3D C

Sales Drawings - Type M3 Switch (SA-M3D)

