CHANCE®

38 kV, 150 kV BIL, 600 A, Polymer (2 1/4" Bolt Circle) insulation, M3 Switch

By CHANCE Utility Catalog # M3D68AP

38kV, 150kV BIL, 600 A, Single-Phase Hookstick Disconnect Switch, ESP insulators and 10" carriage bolts.



*Representative Image

Features

- Fully Compliant with ANSI/IEEE C37.30.1
- 15, 27 & 38kV Voltage Classes
- 110, 125, 150, 200kV BIL Insulation Levels
- 600A & 900A Current Ratings
- Porcelain and ESP Polymer Insulator Assemblies with 2.25" Bolt Circles
- · Distribution Base, Serrated Slots
- · Load Break Option Available

General

Base Type Distribution Base, Serrated

Slots

Blade Type Solid Copper (two blade

truss-member) 800 Lbs (3.56 kN)

Cantilever Bending Strength -

Routine

Color - Insulator Dark Gray
Contact Silver

Description - Terminal 2 - Teminal Connectors

Connectors (ATC1343, #2 - 500kcmil) w/

galvanized hardware

Insulator Type Polymer (2 1/4" Bolt Circle)
Material - Base Galvanized Steel per ASTM

A153

Tension Range 5000 lb

Torsional Strength 3,000 in Lbs (339 N-M)

UPC 096359591573

Dimensions

Bolt Length 10.00 in

Electrical Ratings

Arc Distance - Dry 10" (254mm)
BIL 150 kV

Creep and Leakage Distance 28.2" (716.3mm)

Current Overload - 8hr 1080 A

Emergency

Current Rating 600 A
Dead-Ending Rating - 8,000 Lbs

Working Load

Temperature Rise - Max. at 28°C

600A

Voltage - Maximum 38 kV

Withstand Current - Short

Time (10 cycles)

Withstand Current - Short 25kA, symmetrical

Time (2 sec)

Withstand Current - Short 16kA, symmetrical

Time (3 sec)

Certifications and Compliance

Industry Standard(s)

All Applicable ANSI/IEEE

Standards

40kA, asymmetrical

Logistics

Pallet Quantity 20 Standard Package 1

Product Assets

Catalogs - Hookstick Operated Switches (CA10230E_14B) Installation Manuals - Instructions for CHANCE Type M3

Distribution Switch (P807-0198)

Installation Manuals - Type M3C Single Insulator Disconnect

Switch for Distribution Switching (PSP8070357)

Installation Manuals - M3_Instructions

Literature - SA-M3D C

Sales Drawings - Type M3 Switch (SA-M3D) Technical Solutions - CH-M3D68AP-SPEC-EN

