

15.5 kV, 110 kV BIL, 900 A, Porcelain (2 1/4" Bolt Circle) insulation, M3 Switch

By Chance Catalog # M3D92AP

14.4kV, 110kV, 900 A, Single-Phase Hookstick Disconnect Switch.



*Representative Image

Electrical Ratings

Arc Distance - Dry BIL	6" (152.4mm) 110 kV
Creep and Leakage Distance	10.5″ (266.7mm)
Current Overload - 8hr	1620 A
Emergency	1020 A
Current Rating	900 A
Dead-Ending Rating - Working	8,000 Lbs
Load	-,
Reference Voltage Limit -	14.4kV
Minimum	
Temperature Rise - Max. at	46.7°C
900A	
Voltage - Maximum	15.5 kV
Withstand Current - Short Time	40kA, asymmetrical
(10 cycles)	
Withstand Current - Short Time	25kA, symmetrical
(2 sec)	
Withstand Current - Short Time	16kA, symmetrical
(3 sec)	

Certifications And Compliance

Industry Standard(s)	All Applicable ANSI/IEEE Standards
Logistics	
Pallet Quantity Standard Package	42 1

Product Assets

Catalogs - Hookstick Operated Switches Installation Manuals - Type M3C Single Insulator Disconnect Switch for Distribution Switching Installation Manuals - Instructions for CHANCE Type M3 Distribution Switch Literature - SA-M3D_C Sales Drawings - Type M3 Switch

Features

- Fully Compliant with ANSI/IEEE C37.30.1
- 15, 27 & 38kV Voltage Classes
- 110, 125, 150, 200kV BIL Insulation Levels
- 600A & 900A Current Ratings
- Porcelain and ESP Polymer Insulator Assemblies with 2.25" Bolt Circles
- Distribution Base, Serrated Slots
- Load Break Option Available

General

Base Type	Distribution Base, Serrated Slots
Blade Type	Solid Copper (two blade truss- member)
Cantilever Bending Strength - Routine	1,200 Lbs (5.34 kN)
Catalog Number	M3D92AP
Color - Insulator	Sky Gray
Contact	Silver
Description - Terminal	2 - Teminal Connectors
Connectors	(ATC1343, #2 - 500kcmil) w/ galvanized hardware
Insulator Type	Porcelain (2 1/4" Bolt Circle)
Material - Base	Galvanized Steel per ASTM A153
Tension Range	5000 lb
Torsional Strength	3,000 in Lbs (339 N-M)
UPC	096359530091

Dimensions

Bolt Length

10 in



A Hubbell brand

©2024 Hubbell Incorporated. All rights reserved CH-M3D92AP-SPEC-EN | REV 6/2024