

38 kV, 150 kV BIL, 900 A, Porcelain (2 1/4" Bolt Circle) insulation, M3 Switch

By CHANCE Utility Catalog # M3D94ALR

34.5kV, 150kV, 900 A, Single-Phase Hookstick Disconnect Switch.



*Representative Image

Features

- Fully Compliant with ANSI/IEEE C37.30.1
- 15, 27 & 38kV Voltage Classes
- 110, 125, 150, 200kV BIL Insulation Levels
- 600A & 900A Current Ratings
- Porcelain and ESP Polymer Insulator Assemblies with 2.25" **Bolt Circles**
- · Distribution Base, Serrated Slots
- · Load Break Option Available

General

Base Type Distribution Base. Serrated

Slots

Blade Type Solid Copper (two blade

truss-member)

Cantilever Bending Strength -800 Lbs (3.56kN)

Routine

Color - Insulator Sky Gray Contact Silver

Insulator Type Porcelain (2 1/4" Bolt Circle)

Material - Base Galvanized Steel per ASTM

A153

Tension Range 5000 lb

Torsional Strength 3,000 in Lbs (339 N-M)

Dimensions

Bolt Lenath 10.00 in

Electrical Ratings

Arc Distance - Dry 10" (254mm) 150 kV BII

Creep and Leakage Distance 24" (609.6mm)

Current Overload - 8hr 1620 A

Emergency

Current Rating 900 A Dead-Ending Rating -8,000 Lbs

Working Load

Reference Voltage Limit -34.5kV

Minimum

900A

38 kV Voltage - Maximum

Withstand Current - Short

Temperature Rise - Max. at

Time (10 cycles)

Withstand Current - Short 25kA, symmetrical

Time (2 sec)

Withstand Current - Short 16kA, symmetrical

Time (3 sec)

Certifications and Compliance

Industry Standard(s) All Applicable ANSI/IEEE

Standards

46.7°C

40kA, asymmetrical

Logistics

Pallet Quantity 16 EA Standard Package

Product Assets

Catalogs - Hookstick Operated Switches (CA10230E 14B) Installation Manuals - Instructions for CHANCE Type M3

Distribution Switch (P807-0198)

Installation Manuals - Type M3C Single Insulator Disconnect Switch for Distribution Switching (PSP8070357)

Installation Manuals - M3_Instructions

Literature - SA-M3D C

Sales Drawings - Type M3 Switch (SA-M3D) Technical Solutions - CH-M3D94ALR-SPEC-EN