

38 kV, 150 kV BIL, 900 A, Polymer (2 1/4" Bolt Circle) insulation, M3 Switch

By Chance Catalog # M3D98BCR

38kV, 150kV BIL, 900 A, Single-Phase Hookstick Disconnect Switch, ESP insulators, 10" carriage bolts.

Features

- Fully Compliant with ANSI/IEEE C37.30.1
- 15, 27 & 38kV Voltage Classes
- 110, 125, 150, 200kV BIL Insulation Levels
- 600A & 900A Current Ratings
- Porcelain and ESP Polymer Insulator Assemblies with 2.25" Bolt Circles
- Distribution Base, Serrated Slots
- Load Break Option Available

General

Base Type	Distribution Base, Serrated Slots
Blade Type	Solid Copper (two blade truss- member)
Cantilever Bending Strength - Routine	800 Lbs (3.56 kN)
Catalog Number	M3D98BCR
Color - Insulator	Dark Gray
Contact	Silver
Description - Captive Hardware	Consist of 4 each: 1/2" 13
	Stainless Steel Splined Bolt,
	1/2" Lockwasher and Bronze
	Nut
Insulator Type	Polymer (2 1/4″ Bolt Circle)
Material - Base	Galvanized Steel per ASTM
	A153
Tension Range	5000 lb
Torsional Strength	3,000 in Lbs (339 N-M)
Dimensions	

Dimensions

Bolt Length

8 in



Electrical Ratings


Arc Distance - Dry	10" (254mm)
BIL	150 kV
Creep and Leakage Distance	28.2" (716.3mm)
Current Overload - 8hr	1620 A
Emergency	
Current Rating	900 A
Dead-Ending Rating - Working	8,000 Lbs
Load	
Temperature Rise - Max. at	46.7°C
900A	
Voltage - Maximum	38 kV
Withstand Current - Short Time	40kA, asymmetrical
(10 cycles)	
Withstand Current - Short Time	25kA, symmetrical
(2 sec)	
Withstand Current - Short Time	16kA, symmetrical
(3 sec)	

Certifications And Compliance

Industry Standard(s)	All Applicable ANSI/IEEE Standards
Logistics	
Pallet Quantity Standard Package	16 EA 1

Product Assets

Catalogs - Hookstick Operated Switches Installation Manuals - Type M3C Single Insulator Disconnect Switch for Distribution Switching Installation Manuals - Instructions for CHANCE Type M3 Distribution Switch Literature - SA-M3D_C Sales Drawings - Type M3 Switch



©2024 Hubbell Incorporated. All rights reserved CH-M3D98BCR-SPEC-EN | REV 6/2024