



# SPOOL INSULATOR SECONDARY CLEVIS, w/GRAY ANSI 53-2 INSULATOR

By Chance  
Catalog # [PS0338G532](#)

Clevis bracket for spool insulators used in secondary line deadend applications. Minimum ultimate deadend strength is 4,000 lbs. Used with ANSI Class 53-2 or 53-3 spool insulators. Replacement components: clevis pin - 450033P; cotter pin - 056747P.

## Features

- 11/16" x 1-1/8" mounting hole
- 5/8" dia. clevis pin with self-locking cotter pin
- Hot dip galvanized per ASTM A-153
- Manufactured in compliance with ANSI/IEEE C135.20

## General

Catalog Number	PS0338G532
Coating	Galvanized, ASTM A-153
Material	Steel
Type	Insulated Secondary Clevis
UPC	096359486749

## Dimensions

Dimensions	14.500 in x 1.000 in x 3.25 in
Distance From Pole	N/A
Height	3.25 in



Length	14.5 in
Weight	3.19 lb
Width	1 in

## Certifications And Compliance

Buy America(n) Qualified	TAA Compliant (All status valid till December 2024)
Industry Standard(s)	ANSI C29.3

## Logistics

Carton Quantity	12
Pallet Quantity	432

## Product Assets

- [Catalogs - Pole Line Hardware](#)
- [Sales Drawings - Insulated Clevis](#)
- [Specifications - PS0338G532](#)



A Hubbell brand