



# CROSSARM INSULATOR PIN with 1in LEAD THREAD, 6in SHAFT LENGTH and 3/4in x 1-3/4in SHANK

By Chance  
Catalog # [PS893](#)

Insulator pin used to support pin type insulator with 1" NEMA internal thread on crossarm. Refer to sales drawing link for included hardware.



\*Representative Image

## Features

- Cantilever load rating is 1,400 lbs. based on ANSI/IEEE 10 degree deflection criteria
- Minimum thread length of shank is 1-1/2"
- Galvanized steel per ASTM A-153

## General

|                |                        |
|----------------|------------------------|
| Catalog Number | PS893                  |
| Coating        | Galvanized, ASTM A-153 |
| Material       | Steel                  |
| Type           | Pins                   |
| UPC            | 096359076025           |

## Dimensions

|                        |                                |
|------------------------|--------------------------------|
| Dimensions             | 8.125 in x 2.500 in x 2.500 in |
| Distance From Pole     | N/A                            |
| Height                 | 2.5 in                         |
| Length                 | 8.125 in                       |
| Length - Threaded Area | 1.75                           |
| Weight                 | 1.73 lb                        |
| Width                  | 2.5 in                         |

## Certifications And Compliance

|                      |              |
|----------------------|--------------|
| Industry Standard(s) | ANSI C135.17 |
|----------------------|--------------|

## Logistics

|                 |      |
|-----------------|------|
| Pallet Quantity | 1200 |
|-----------------|------|

## Product Assets

[Catalogs - Pole Line Hardware](#)  
[Sales Drawings - SA893 \(For Reference Only\)](#)