



## FLAT APITONG WOOD CROSSARM BRACE, 26in MOUNTING HOLE SPACING, 13/16in x 1-3/4in MATERIAL SIZE. SOLD in PAIRS.

By Chance  
Catalog # [PSCRAF626](#)



\*Representative Image

Flat wood crossarm braces are installed as pairs in a V-type configuration to the side of crossarm and pole face to strengthen the crossarm and provide stability. Order quantity of one pair for one V-type installation.

### Features

- 7/16" dia. crossarm hole and 9/16" pole hole
- Tongue and groove fitting/wood connection captured with nail through both wood and aluminum
- Pole end fitting offset is reversed from standard PSCAF626 orientation
- End fittings are 6061-T6 aluminum
- Brace member is Apitong wood, pressure treated with copper naphthenate per AWPA P8 standards

### General

|          |  |
|----------|--|
| Material | Apitong Wood w/ 6061-T6<br>Aluminum Fittings |
| UPC      | 096359531470                                 |

### Dimensions

|                    |     |
|--------------------|-----|
| Distance From Pole | N/A |
|--------------------|-----|

### Logistics

|                 |     |
|-----------------|-----|
| Pallet Quantity | 400 |
|-----------------|-----|

### Product Assets

- [Sales Drawings - Flat Apitong Brace](#)
- [Sales Drawings - Flat Apitong Brace](#)



A Hubbell brand