



**FLAT APITONG WOOD CROSSARM  
BRACE, 26in MOUNTING HOLE  
SPACING, 13/16in x 1-3/4in  
MATERIAL SIZE. SOLD in PAIRS.**

By Chance  
Catalog # [PSCRAF626P1116](#)

Flat wood crossarm braces are installed as pairs in a V-type configuration to the side of crossarm and pole face to strengthen the crossarm and provide stability. Order quantity of one pair for one V-type installation.

**Features**

- 7/16" dia. crossarm hole and 11/16" pole hole
- Tongue and groove fitting/wood connection captured with nail through both wood and aluminum
- Pole end fitting offset is reversed from standard PSCAF626 orientation
- End fittings are 6061-T6 aluminum
- Brace member is Apitong wood, pressure treated with copper naphthenate per AWWA P8 standards

**General**



\*Representative Image

Catalog Number	PSCRAF626P1116
Material	Apitong Wood w/ 6061-T6 Aluminum Fittings

**Dimensions**

Distance From Pole	N/A
--------------------	-----

**Product Assets**

- [Sales Drawings - Flat Apitong Brace](#)
- [Sales Drawings - Flat Apitong Brace](#)
- [Specifications - PSCRAF626P1116](#)



A Hubbell brand