



## SPOOL INSULATOR SECONDARY DEADEND CLEVIS, w/GRAY ANSI CLASS 53-2 INSULATOR

By Chance  
Catalog # [T2070085](#)



Clevis bracket for spool insulators used in secondary deadend applications. Minimum ultimate deadend strength is 4,000 lbs. Used with ANSI Class 53-2 and 53-3 spool insulators. Replacement components: clevis pin - 450033P; cotter pin - 056747P.

### Features

- 1-1/2" x 1/2" x 1/8" channel material
- 11/16" x 7/8" dia. mounting hole
- 5/8" dia. clevis pin with self-locking cotter pin
- Hot dip galvanized per ASTM A-153
- Manufactured in compliance with ANSI/IEEE C135.20, item 4

### General

Catalog Number	T2070085
Coating	Galvanized, ASTM A-153
Material	Steel
Type	Insulated Secondary Clevis
UPC	096359057505

### Dimensions

Dimensions	6.000 in x 5.000 in x 3.25 in
Distance From Pole	N/A
Height	3.25 in
Length	6 in
Weight	2.65 lb
Width	5 in

### Logistics

Pallet Quantity	600
-----------------	-----

### Product Assets

[Catalogs - Pole Line Hardware](#)  
[Sales Drawings - Insulated Clevis](#)