



## Two Conductor Supports

By Chance Lineman Tools & Equipment  
Catalog # C4001509



This Epoxiglas® temporary conductor support is used to hold energized distribution conductors during replacement of poles or repair or replacement of pole top and stand-off insulators; it is furnished with wheel tightener for poles up to 14" in diameter. Fork-type, 1.5" wireholder is standard equipment or the 2.5" diameter Epoxiglas standoff, accommodating conductor sizes up to 1" in diameter. Working load: 150 lb. per wireholder. For 34.5 kV or when the tool is to support an energized conductor overnight or during periods of expected rain, M4805-7 insulators should be added to the wireholders.

### Features

- Epoxiglas™ temporary conductor support is used to hold energized distribution conductors
- For use during replacement of poles or repair/replacement of pole top and stand-off insulators
- Features wheel tightener for poles up to 14" in diameter
- M480517 fork-type, 1" wireholder is standard
- Working load: 150 lb. per wireholder
- Rated 100 lbs., Side Load, Max.

### General

Style Chainbinder Style  
UPC 096359017073

### Dimensions

Dimensions	48.19 in x 6.63 in x 6.5 in
Height	6.5 in
Length	48.19 in
Length Metric	122.4 mm
Weight	26.5 lb
Weight Metric	12.0 kg
Width	6.63 in

### Logistics

Pallet Quantity 25

### Product Assets

[Catalogs - Conductor Support Equipment \(2200\)](#)  
[Installation Manuals - CHANCE® Tools Manuals \(CENT\\_LTE\\_IOM\\_EN\\_00158\)](#)  
[Technical Solutions - CH-C4001509-SPEC-EN](#)



A proud member of the Hubbell Family.

©2024 Hubbell Incorporated. All rights reserved.  
CLTE-C4001509-SPEC-EN | REV 1/2024