

Adjustable Strain Pole, 18 ft (5.4 m), 5 Pins

By Chance Lineman Tools & Equipment Catalog # C4012149

POLE, ADJUSTABLE STRAIN, Key to many transmission and EHV maintenance jobs, these hot-line tools help support conductors while insulators are removed and replaced. Adjustable strain poles can be used with yoke plates and hook assemblies at the conductor and structure ends of suspension, V-string or deadend insulator strings. To support the hot-end trunnions or hooks, five stainless steel crosspins are located at 6" intervals on the 2"-diameter Epoxiglas ™ poles. To engage deadend and suspension yokes at the hot end also requires the adjustable pole clamp of heat-treated aluminum. This pole clamp can be unlocked and positioned by hotsticks. On the cold end, a high-strength steel strain-jack with bronze tongue provides take-up with a ratchet wrench and trunnions. Wrench and trunnions must be ordered as separate items. Standard strain jack furnished with each strain pole provides 12" of adjustment. Longer strain jacks (for 24" or 36" of take-up) and extra pole clamps also may be ordered.

Features

- Tested per OSHA & ASTM F711
- For many transmission and EHV maintenance applications
- Help support conductors while insulators are removed and replaced
- Used with yoke plates and hook assemblies at the conductor
- Also used for structure ends of suspension, V-string or deadend insulator strings
- 5 stainless-steel crosspins are located at 6" intervals on the 2"-diameter Epoxiglas ™ poles to support hot-end trunnions or hooks
- Engaging deadend and suspension yokes at the hot end also require the adjustable, heat-treated aluminum pole clamp
- Pole clamp can be unlocked and positioned by hotsticks
- On cold end, a high-strength steel strain-jack with bronze tongue provides take-up with a ratchet wrench (see page 2257) and trunnions (page 2255)) (Wrench and trunnions must be ordered as separate items)
- Standard strain jack included with each strain pole provides 12" of adjustment

General

| EU RoHS Indicator | No |
|-------------------|--------------|
| Style | Adjustable |
| UPC | 096359017752 |



*Representative Image

Dimensions

| Dimension - L Length Overall mm | 5.9 m |
|------------------------------------|----------------------|
| Dimension - Length Overall inch | 19.66 ft |
| Dimensions | 236 in x 6 in x 6 in |
| Height | 6 in |
| Length | 236 in |
| Length - Insulated Section | 180.0 in |
| Length Metric | 599.4 mm |
| Lengths - Extended | 236 |
| Weight | 39.0 lb |
| WeightMetric | 17.6 kg |
| Width | 6 in |
| | |

Electrical Ratings

Voltage - Maximum 765 kV

Product Assets

Installation Manuals - CHANCE® Tools Manuals (CENT_LTE_IOM_EN_00158)<LineBreak/> Literature - Transmission Project Tools and Equipment Checklist (CENT_LTE_FRM_EN_00082)

Related Products

E4011998P - Tongue Type Strain Jack for Strain Poles, 12 in (0.3 m) 059738P - Klik Pin, 0.187 X 1.562 in E4010138P - Pole Clamp for Adjustable Strain Poles E4011510P - Steel Through Pin for Adjustable Strain Poles



A proud member of the Hubbell Family.