

## Heavy Duty Two-Pole Strain Carrier, 12 ft (3.6 m)

By Chance Lineman Tools & Equipment  
Catalog # [C4012216](#)

Two-pole Strain Carriers relieve strain from an insulator string to permit removal from energized lines. Normally used on a single string of insulators, these carriers sometimes are used for multiple strings where conductor-end hardware permits attachment. Yokes are fabricated from high-strength aluminum plate and include a steel chain assembly for anchoring the back plate to the structure. Conductor-end yoke includes a hook and three machined sockets (C401-1860, -1892, -1894). Two-pole Strain Carriers relieve strain from an insulator string to permit removal from energized lines. Normally used on a single string of insulators, these carriers sometimes are used for multiple strings where conductor-end hardware permits attachment.

### Features

- Tested per OSHA & ASTM F711
- Relieve strain from an insulator string to permit removal from energized lines
- Normally used on a single string of insulators
- Also used for multiple strings where conductor-end hardware permits attachment
- Available here as complete assemblies – separate components may also be ordered
- Yokes are fabricated from high-strength aluminum plate
- Feature a steel chain assembly for anchoring the back plate to the structure
- Conductor-end yoke includes a hook and a machined socket (C4011894)

### General

EU RoHS Indicator	No
Style	Two Pole Strain Carrier - Transmission
UPC	096359234876



### Dimensions

Length	144 in
Length Metric	365.8 mm
Maximum Distance Between Yokes	147 in
Maximum Distance Between Yokes Metric	373.3 cm
Minimum Distance Between Yokes	113 in
Minimum Distance Between Yokes Metric	287 cm
Weight	95 lb
WeightMetric	43.1 kg

### Electrical Ratings

Voltage - Maximum	362000 V
-------------------	----------

### Product Assets

[Installation Manuals - CHANCE® Tools Manuals Literature - Transmission Project Tools and Equipment Checklist](#)



A Hubbell brand

©2024 Hubbell Incorporated. All rights reserved  
CLTE-C4012216-SPEC-EN | REV 6/2024