

## **Elbow Tool, Hammer Type**

By Chance Lineman Tools & Equipment Catalog # C4031851

These tools facilitate removing elbow connectors from bushings of transformers and other apparatus. Elbows that have been installed for a long period of time sometimes are difficult to remove because silicone grease on the interface of the elbow and bushing dries out and hardens. A special integral hook on the tool heat fits through the rubber eye of an elbow or the metal hook of a bushing cap. Used in this manner, the hook adds extra control and pulling power to the grippers. Design Features The lightweight tool employs a simple, slide-hammer mechanism to easily disengage and assist in replacing elbows. The tool and grippers help the operator control the elbow and stiff underground cable lead. For a sure, balanced grip the 5-pound slide hammer is plastisol coated and flared at both ends. Also for secure handling, both front and rear handgrip areas of the pole are coated with Griptread, a grit-filled rubber-base paint. Operation To pull an elbow connector: Insert hook through eye on elbow. Close down grippers on elbow by rotating pole. Support tool with one hand on front grip behind handguard and other hand on slide hammer. Slam hammer from front to rear anvil. Resulting impact should release elbow with sufficient momentum to withdraw it from the bushing without extended arcing. To replace an elbow connector: Follow the same procedures for pulling except use slide hammer impact against front anvil to help seat the elbow.



\*Representative Image

## General

EU RoHS Indicator No

Storage Bag Included? P643-6 (Bag not included.

Must be ordered separately.)

Style Impact Elbow Puller
Type Underground Tools
UPC 096359019565

## **Dimensions**

Dimensions 66 in x 4.38 in x 4.38 in

Height 4.38 in
Length 66 in
Length Metric 167.6 mm
Weight 14.0 lb
WeightMetric 6.4 kg
Width 4.38 in

## **Product Assets**

Catalogs - Insulated Hand Tools (2100) Sales Drawings - Hammer Type Elbow Tool (SAC4031822)

