

## Swivel Boom, 10 ft (3.0 m) with 6 ft (1.8 m) Mast

By Chance Lineman Tools & Equipment  
Catalog # [H1973H10](#)



BOOM, SWIVEL, The medium duty Swivel Boom assembly is used on transmission structures to lift and move the insulator cradle and insulators into a convenient work position on the structure. The 3" round Epoxiglas®- horizontal boom and vertical mast are designed for 500 pound ratings when used in a steel tower configuration and 600 pound rating for wood pole assembly. An insulated link stick and a hoist are used in a diagonal position to lift the cradle full of insulators clear of the deadend strain poles and other obstructions.

### Features

- Used on transmission structures to lift and move an insulator cradle with insulators into a convenient work position on a structure
- 3"-round Epoxiglas™ horizontal boom and vertical mast are designed for 500-lb. ratings when used in a steel-tower configuration
- 600-lb. rating for wood-pole assembly
- Insulated link stick and hoist are used in diagonal position to lift cradle full of insulators clear of deadend

### General

EU RoHS Indicator	No
Type	Boom
UPC	096359039624

### Dimensions

Length	10 ft
Weight	61 lb
WeightMetric	27.7 kg

### Product Assets

[Catalogs - Load Handling Accessories](#)  
[Installation Manuals - CHANCE® Tools Manuals](#)