

Wire Tong - 1.5 in x 10 ft

By Chance Lineman Tools & Equipment Catalog # H464510

Wire Tongs have many applications for moving and holding live conductors clear of the working area, for flat crossarm and/or ridge pin-construction, on horizontal post insulator structures, all types of suspension insulator lines, as auxiliary arm braces, and in EHV construction for brace pole or ladder positioning guides. A whole family of clamps, attachments, saddles and lever lifts allow the wire tongs to be adapted specifically to the mechanical requirements of various maintenance jobs. Wire Tongs are made with Epoxiglas ™ poles. The castings are made of heat treated aluminum alloy, separated by bronze wear rings. The wide range jaws on the head can be clamped tightly on the conductor by turning the stick from a position beyond the minimum working clearances.



Epoxiglas [™] Pole is tested per ASTM F711 AND IEC 60855

Wire Sizes: 0.16" - 2.25"

• Pole Diameter and Length: 1.5" x 10'

• Overall Length: 10' 7.5"

• Mechanical Working Load:

• Cantilever values, with a safety factor of more than two: 1.5" -

• Tensile strength values, with a safety factor more than two: 1.5" - 1500 lb.

General

Catalog Number H464510 Diameter - Pole 1.5 in Diameter - Pole Metric 38.1 mm

Standard Conductor Duty

EU RoHS Indicator

Storage Bag Included? P621-10 (Bag not included. Must be ordered separately.)

Wire Tong

Type **UPC** 096359040446

Dimensions



Dimensions 132 in x 5.25 in x 5.25 in

Dimensions Metric 335.3 mm x 13.3 mm x 13.3 mm

Height 5.25 in 13.3 mm Height Metric Length 132 in 335.3 mm Length Metric Weight 17 lb 7.7 kg WeightMetric Width 5.25 in WidthMetric 13.3 mm

Conductor Related

Wire Size .16 in (4 mm) - 2.25 in (57 mm)

Certifications And Compliance

Buy America(n) Qualified Contact Manufacturer

Product Assets

Catalogs - Conductor Support Equipment

Installation Manuals -

CENT LTE WireTongManual 2022 IOM EN 00158

Installation Manuals - CHANCE® Epoxiglas™ Live-Line Tool

Instruction Manual

Specifications - H464510

