

Roller Link Stick, 82 in (2.0 m), 1.25 in (32 mm) dia.

By Chance Lineman Tools & Equipment Catalog # H47146

ROLLER TYPE LINK STICK-1.25X82 1000LBRWL, The Roller Link Stick is used to spread and hold conductors aside at midspan when relocating poles. It is applied to the conductor at the pole and pulled to position by a hand line attached to the butt ring. The handline should be secured by a temporarily installed screw anchor or other fixed object. The tool is also used for measuring conductor-to-ground clearance by attaching a measuring tape or length of rope to the butt ring. Poles for Roller Link Sticks are 13/4 inches ...rotating the pole closes the hook ... leaving the head free to roll along the conductor.

Features

- Tested per OSHA & ASTM F711
- For spreading and holding conductors at midspan when relocating poles
- Applied to conductor at pole and pulled to position by hand line on butt ring
- Handline should be secured by a temporarily installed screw anchor or other fixed object
- Also used for measuring conductor-to-ground clearance by attaching measuring tape or length of rope to butt ring
- 1-1/4" pole
- Rotating the pole closes the hook, leaving head free to roll along the conductor

General

Duty	1,000 lbs. (454 kg)
EU RoHS Indicator	No
Style	Roller Link Stick
UPC	096359040637
Working Load Limit	1,000 lb
Working Load Limit Metric	453.5 kg

*Representative Image

Dimensions

Diameter	1.25 in
Diameter - Metric	31.7 mm
Dimension - L Length Overall	1.8 m
mm	
Dimension - Length Overall	6 ft
inch	
Dimension - Maximum	605 kcmil ACSR
Conductor Size	
Accommodated	
Dimensions	87 in x 4.38 in x 4.38 in
Dimensions Metric	221.0 mm x 11.1 mm x 11.1 mm
Height	4.38 in
Height Metric	11.1 mm
Length	87 in
Length Metric	221 mm
Lengths - Extended	82
Weight	5 lb
WeightMetric	2.3 kg
Width	4.38 in
WidthMetric	11.1 mm
Conductor Delated	
Conductor Related	

Wire Size

Product Assets

Installation Manuals - CHANCE® Tools Manuals Literature - Transmission Project Tools and Equipment Checklist Sales Drawings - SA4714-6

605 kcmil ACSR



A Hubbell brand

©2024 Hubbell Incorporated. All rights reserved CLTE-H47146-SPEC-EN | REV 6/2024