

Spiral Link Stick, 31 in (0.7 m), 1.25 in (32 mm) dia.

By Chance Lineman Tools & Equipment
Catalog # [H4722](#)

The 31" Spiral Link Stick is used in lieu of a strain link stick in close places where the lineman cannot safely install a strain link stick by hand. A lifting eye on the head ferrule enables the lineman to guide the Spiral Link Stick to the conductor with a hotstick. The pole of the Spiral Link Stick is made of 1-1/4" Epoxiglas™. Ferrule castings are of heat-treated aluminum alloy; spiral hook and butt ring of galvanized steel.

Features

- Tested per OSHA & ASTM F711
- Replaces strain link stick when lineman cannot safely install one by hand
- A lifting eye on the head ferrule enables the lineman to guide the Spiral Link Stick to the conductor with a hotstick
- 1-1/4" Epoxiglas™ pole
- Heat-treated aluminum alloy ferrule castings
- Galvanized-steel spiral hook and butt ring

General

Catalog Number	H4722
Max Load Lbs.	3500 lb
Style	Spiral Link Stick
UPC	096359040835
Working Load Limit	3,500 lb
Working Load Limit Metric	1,587.5 kg

Dimensions

Diameter	1.25 in
Diameter - Metric	3.7 mm
Dimension - L Length Overall mm	393.8 mm
Dimension - Length Overall inch	15.5 in



*Representative Image

Dimension - Maximum Conductor Size Accommodated	1510.5 kcmil ACSR
Dimensions	34.5 in x 7.25 in x 7.25 in
Dimensions Metric	87.6 mm x 18.4 mm x 18.4 mm
Height	7.25 in
Height Metric	18.4 mm
Length	34.5 in
Length Metric	87.6 mm
Weight	7 lb
WeightMetric	3.2 kg
Width	7.25 in
WidthMetric	18.4 mm

Conductor Related

Conductor Diameter (Main) - Maximum	1.5 in
Wire Size	1510.5 kcmil ACSR

Logistics

Pallet Quantity	32
-----------------	----

Product Assets

[Installation Manuals - CHANCE® Tools Manuals](#)
[Literature - Transmission Project Tools and Equipment Checklist](#)
[Sales Drawings - SA_H4722_A](#)
[Specifications - H4722](#)