

Extension Arm, 2.5 in X 5 ft

By Chance Lineman Tools & Equipment
 Catalog # [H480060](#)

EXTENSION ARM 2.5IN X 60IN LONG - 1 WH, The Epoxiglas™ Extension Arm is designed for use on voltages up to and including 15 kV where reconductoring or insulator replacement is necessary. The Epoxiglas Extension Arm can be used on voltages up to 34.5 kV providing the wireholders are fitted with M4805-7 insulators. The Extension Arm is suspended under the crossarm by brackets to enable to conductor to be removed from the original crossarm and placed in the wireholder mounted on the Epoxiglas Extension Arm.

Features

Extension Arm installed on crossarm. Unit is shown here equipped with M4805-7 insulators on the wireholders. Order insulators separately.

General

Catalog Number	H480060
Duty	Standard Duty
EU RoHS Indicator	No
Number of Wireholders	1
Type	Arm
UPC	096359040910
Working Load Limit	150 lb
Working Load Limit Metric	68 kg

Dimensions

Dimensions	12 in x 9 in x 61 in
Dimensions Metric	30.5 mm x 22.9 mm x 154.9 mm
Height	61 in



Height Metric	154.9 mm
Length	12 in
Length Metric	30.5 mm
Weight	22 lb
WeightMetric	10 kg
Width	9 in
WidthMetric	22.9 mm

Certifications And Compliance

Buy America(n) Qualified	Contact Manufacturer
--------------------------	----------------------

Logistics

Pallet Quantity	12
-----------------	----

Product Assets

- [Catalogs - Conductor Support Equipment](#)
- [Installation Manuals - CHANCE® Epoxiglas™ Live-Line Tool](#)
- [Instruction Manual](#)
- [Sales Drawings - Epoxiglas Extension Arm](#)
- [Specifications - H480060](#)