

Single Conductor Support

By Chance Lineman Tools & Equipment
Catalog # [H4809W](#)



This Epoxiglas® temporary conductor support is used to hold energized distribution conductors during replacement of poles or repair or replacement of pole top and stand-off insulators; it is furnished with wheel tightener for poles up to 14" in diameter. Fork-type, 1.5" wireholder is standard equipment or the 2.5" diameter Epoxiglas standoff, accommodating conductor sizes up to 1" in diameter. Working load: 150 lb. per wireholder. For 34.5 kV or when the tool is to support an energized conductor overnight or during periods of expected rain, M4805-7 insulators should be added to the wireholders.

Features

- Epoxiglas™ temporary conductor support is used to hold energized distribution conductors
- For use during replacement of poles or repair/replacement of pole top and stand-off insulators
- Features wheel tightener for poles up to 14" in diameter
- M480517 fork-type, 1" wireholder is standard
- Working load: 150 lb. per wireholder
- Rated 100 lbs., Side Load, Max.

General

Style	Chainbinder Style
UPC	096359040934

Dimensions

Dimensions	48.56 in x 6.19 in x 6.19 in
Dimensions Metric	123.3 mm x 15.7 mm x 15.7 mm
Height	6.19 in
Height Metric	15.7 mm
Length	48.56 in
Length Metric	123.3 mm
Weight	17.5 lb
WeightMetric	7.9 kg
Width	6.19 in
WidthMetric	15.7 mm

Logistics

Pallet Quantity	42
-----------------	----

Product Assets

[Installation Manuals - CHANCE® Tools Manuals](#)



A Hubbell brand