

# Epoxiglas Heavy Duty Swivel Hook Ladder W/14" Hooks, 10'

By Chance Lineman Tools & Equipment Catalog # H490510A

Epoxiglas Hook Ladders have many applications in high voltage maintenance to position linemen in the most advantageous working location, making line repairs possible at otherwise almost unaccessible places. All hooks are formed from 1"-diameter tempered steel and can be swiveled to best fit various angles on the structure. Steel chains clip to the hooks to assist in securing the ladder to a support. Rung material for both rated ladders are 1.25" Epoxiglas, sand coated.

### **Features**

- Meets ASTM F711 and IEC 61478 Category 2
- Designed to effectively position linemen for high-voltage maintenance
- Make line repairs possible, even in inaccessible places
- Two basic styles of Epoxiglas Hook Ladders are available -Regular Duty Ladders with 2" siderails for vertical suspension applications and Heavy Duty Ladders with 2-1/2" siderails for tagged-out positions
- Hooks are formed from 1"-diameter tempered steel
- These hooks can be swiveled to best fit various angles on structure
- Ladders include 8"-dia. hooks
- 14"- or 18"-dia. hooks can be ordered for other structure applications
- Steel chains clip to hooks to assist in securing ladder to support
- Rung material for both rated ladders are 1-1/4" sand-coated Epoxialas

## General

Catalog Number H490510A Strength Rating - Ultimate 1000 lb

Style Swivel Hook Ladder



\*Representative Image

UPC 096359828037

### **Dimensions**

Diameter 2.5 in
Diameter - Hook 14 in

Dimensions 120 in x 27 in x 252 in

Dimensions Metric 304.8 mm x 68.6 mm x 640.1

mm

Height 252 in Height Metric 640.1 mm Length 120 in 304.8 mm Length Metric Side Rail Space 15 in 196 lb Weight WeightMetric 88.9 kg Width 27 in WidthMetric 68.6 mm

## **Product Assets**

Catalogs - Ladders & Platforms
Installation Manuals - CHANCE® Epoxiglas™ Live-Line Tool
Instruction Manual
Literature - Transmission Project Tools and Equipment Checklist
Sales Drawings - SA\_H4905
Specifications - H490510A

