

# Epoxiglas Heavy Duty Swivel Hook Ladder W/18" Hooks, 20'

By Chance Lineman Tools & Equipment Catalog # H490520B


LADDER, 2.5X20'W/18" HOOKS, Epoxiglas Hook Ladders have many applications in high voltage maintenance to position linemen in the most advantageous working location, making line repairs possible at otherwise almost unaccessible places. All hooks are formed from 1"-diameter tempered steel and can be swiveled to best fit various angles on the structure. Steel chains clip to the hooks to assist in securing the ladder to a support. Rung material for both rated ladders are 1.25" Epoxiglas, sand coated.

### Features

- Meets ASTM F711 and IEC 61478 Category 2
- Designed to effectively position linemen for high-voltage maintenance
- Make line repairs possible, even in inaccessible places
- Two basic styles of Epoxiglas Hook Ladders are available -Regular Duty Ladders with 2" siderails for vertical suspension applications and Heavy Duty Ladders with 2-1/2" siderails for tagged-out positions
- Hooks are formed from 1"-diameter tempered steel
- These hooks can be swiveled to best fit various angles on structure
- Ladders include 8"-dia. hooks
- 14"- or 18"-dia. hooks can be ordered for other structure applications
- Steel chains clip to hooks to assist in securing ladder to support
- Rung material for both rated ladders are 1-1/4" sand-coated Epoxiglas

#### General

EU RoHS Indicator	No
Strength Rating - Ultimate	750 lb
Style	Swivel Hook Ladder
UPC	096359314622



\*Representative Image

## Dimensions

Diameter	2.5 in
Diameter - Hook	18 in
Dimensions	240 in x 27 in x 252 in
Height	252 in
Length	240 in
Length Metric	609.6 mm
Side Rail Space	15 in
Weight	317 lb
WeightMetric	143.8 kg
Width	27 in

## **Product Assets**

Catalogs - Ladders & Platforms (2350) Installation Manuals - CHANCE® Tools Manuals (CENT\_LTE\_IOM\_EN\_00158)<LineBreak/> Literature - Transmission Project Tools and Equipment Checklist (CENT\_LTE\_FRM\_EN\_00082) Sales Drawings - SA\_H4905

