



# Static Ground with Eye-Screw Clamp



By Chance Lineman Tools & Equipment  
Catalog # [HG42301](#)

Designed to eliminate the problem of electrostatic charge when working insulator strings. The Static Ground drains off the charge from the insulator string to the tower leg. Six feet of No. 2 grounding cable is attached to the Static Ground tool and a flat face clamp attaches to the either end of the grounding cable. The adjustable jaws of the Static Ground fit insulator caps from 2 1/2" to 6". Overall length with a 1 1/4" x 19" Epoxiglas™ pole, is 30". To ground an insulator string, attach the flat face clamp to the tower leg and the Static Ground just under the first insulator cap. For barehand work, attach the flat face clamp to the bucket shield system and the Static Ground under the second insulator from the LIVE end.

## General

EU RoHS Indicator	No
Style	w/ Eyescrew Clamp No. G3363-3SJ
UPC	096359038795

## Dimensions

Dimensions	34 in x 6.25 in x 6.25 in
Height	6.25 in
Length	34 in
Length Metric	86.4 mm
Weight	5.1 lb
WeightMetric	2.3 kg
Width	6.25 in

## Logistics

Pallet Quantity	56
-----------------	----

## Product Assets

[Literature - Transmission Project Tools and Equipment Checklist \(CENT\\_LTE\\_FRM\\_EN\\_00082\)](#)



A proud member of the Hubbell Family.