

# Wire-Ready Foundation, 6-5/8" OD x 96" Long

By CHANCE Foundation Solutions Catalog # T1120564

FOUNDATION, SLF 6.625 OD x 96" Long, 1" thick x 12" square baseplate, variable circle, hardware included.



\*Representative Image

#### **Features**

- Variable 8" 14" Bolt Circle
- 4 slots, 1" Dia x 4" Long
- Suitable for Streetlight, Roadway, and Architectural
- Other applications include EV Charging Infrastructure, 5G/6G Poles, Rail Applications, End Zone Tower Systems, Solar Array Pole Mount, and Signage

#### **Application**

Helical Anchoring

#### General

UPC

With Hardware

Base Plate Shape	Square
Bolt Hole Type	Slotted
Coating	Galvanized, ASTM A-153
EU RoHS Indicator	No
Ground Lug Hole	No
Hardware Packaging	Installed
Number of Bolt Slots	4
Pipe Type	Round Pipe
Type	Lighting Foundation Anchors

096359242260

Included

## **Dimensions**

Base Plate Dimensions	12.00 in
Base Plate Thickness	1.000 in
Bolt Length	4.00 in
Cableway Distance From Base	48 in
Cableway Length	18.00 in
Cableway Width	3.00 in
Center hole dimensions	5.00 in
Diameter - Bolt	1 in
Diameter - Bolt Circle	• 8 in
	• 14 in
Foundation Diameter	6.630 in
Foundation Length	96 in
Weight	192.000 lb

#### Logistics

Pallet Quantity	9
Standard Package	1

## **Product Assets**

Case Studies - Case History - Randazzo Park (CH04318E_1120) Engineering Drawing - SA1120564
ISO Certificates - Centralia Operations ISO 9001 2015
Literature - Instant Foundation Solutions (SF04248E_0819)
Literature - Precast Concrete Collars (SF04273E)
Literature - Instant Foundations and Pre-Cast Concrete Collars
(BR04331E)
Literature - Instant Foundations® for EV Charging Stations
(SF04048E)
Sales Drawings - 8" - 14" B.C. Lighting Foundation 6" X 96"
(SA112-0564_C)

SDS - MSDS - Galvanized Steel Products

Test Documents - Pole Load Determination Data Sheet (TD04196E)

Video - CHANCE Instant Foundation & Concrete Collar (VIO4163E0520)

Video - SLF (VIO4173E1021)

Video - CHANCE® Instant Foundation System (VIO4150E\_14L)

## **Related Products**

C3030139



CN-11120304-3PEC-EN | REV 1/2023