

Steel Service Saddle Punch Tee

By Continental Industries (CI) Catalog # 120121100400

SADDLE PUNCH TEE, 4IN IPS MAIN-1/2IN IPS BODY X, 1/2" CTS .090 PE COMP, 3/8" CR PUNCH



Features

- RUGGED ALL STEEL CONSTRUCTION
- FULL WRAP AROUND
- ELASTOMERIC O-RING SEAL
- EXCLUSIVE HINGE CONSTRUCTION
- USES SINGLE ZINC DICHROMATE PLATED NUT AND BOLT
- CAN BE USED FOR KEY HOLE APPLICATIONS
- CAP SCREWS DOWN INSIDE TEE BODY
- O-RING IN CAP PREVENTS LEAKAGE
- NO NEED FOR TEFLON TAPE OR THREAD SEALANT
- CAP CAN BE TIGHTENED BY HAND TO SEAL AT 450 PSI
- WELDS ARE TESTED TO 450 PSI
- PUNCH PROVIDES POSITIVE VALVE ACTION AT MAIN
- FAST NO BULKY DRILLING EQUIPMENT NEEDED
- SAFE NO BLOWING OF GAS
- CAN BE FURNISHED WITH ANY TYPE CONTINENTAL
 OUTLET
- TWO TYPES OF PUNCHES AVAILABLE
- AVAILABLE IN WELD, THREADED OR SADDLE INLETS

General

Material

Steel

Product Assets

Installation Manuals - CONT-Manual-0000-34-6034-90-steelservice-punch-tee Installation Manuals - CONT-Manual-0000-34-6034-91-steelservice-punch-tee

