Steel Service Punch Tee

By Continental Industries
Catalog # 130209081300

PUNCH TEE, 3/4IN IPS BODY-WB X 3/4IN IPS BW, 3/8" CR PUNCH with Weld Outlet

Features

- CAP SCREWS DOWN INSIDE TEE BODY
- O-RING IN CAP PREVENTS LEAKAGE
- NO NEED FOR TEFLON TAPE OR THREAD SEALANT
- CAP CAN BE TIGHTENED BY HAND TO SEAL AT 450 PSI
- WELDS ARE TESTED TO 450 PSI
- PUNCH PROVIDES POSITIVE VALVE ACTION AT MAIN
- FAST - NO BULKY DRILLING EQUIPMENT NEEDED
- SAFE - NO BLOWING OF GAS
- CAN BE FURNISHED WITH ANY TYPE CONTINENTAL OUTLET
- TWO TYPES OF PUNCHES AVAILABLE
- AVAILABLE IN WELD, THREADED OR SADDLE INLETS

Application

3/4IN IPS BODY-WB X 3/4IN IPS BW, 3/8"

General

Material	Steel

Product Assets

Catalogs - Wholesale Distribution Catalog
Catalogs - CONT_Steel-Punch-Tees-Connector-Catalog
Installation Manuals - CONT-Manual-0000-34-7144-49-steel-service-punch-tee
Installation Manuals - CONT-Manual-0000-34-6034-53-service-punch-tee

©2024 Hubbell Incorporated. All rights reserved.