HUBBELL **Power Systems**

Distribution Arresters NLZ-P 10 kV

By Delmar Catalog # NLZP-1010

The polymer distribution arresters model NLZ-P are designed to protect equipment against surges in distribution lines. UV resistant silicone rubber housing. Arresters are supplied with automatic ground lead disconnector. Assembled and tested in

Manufactured with metal oxide varistors without series gaps and accordance to ABNT / ANSI / IEC standards.

Features

- Available in the rating of 3 kV to 36kV 10kA
- · Hot dip galvanized NEMA bracket
- · Polymer insulating bracket
- Line and ground terminals for 10 to 2/0AWG cables
- High relief identification on the housing

General

Catalog Number NLZP-1010 Residual Voltage (1? (max.)) 35.90 Residual Voltage (8 x 20? 32.00 (max.))



*Representative Image

Dimensions

Height 250 mm 100 mm Length

Electrical Ratings

Creep and Leakage Distance 430 mm Operating Voltage 8400 VAC Voltage Rating 10 kV

Product Assets

Catalogs - Para-raios de Distribuição NLZ-P 3kV a 36kV Literature - Hubbell Arrester and Wildlife Guard Solution Kits Literature - Application Guide: Metal-oxide Surge Arresters for use on AC systems

