HUBBELL Power Systems

Station Class Arresters ZYP 27 kV

By Delmar Catalog # ZYP2710

The class II polymer substation arresters model ZYP are designed to protect equipment against surges in substations. Manufactured with metal oxide varistors, without series gaps and UV resistant silicone rubber housing. Arresters are supplied with tripod base for structure mounting. Assembled and tested in accordance to ABNT / ANSI / IEC standards.

Features

- Available in the rating of 9kV to 144kV 10kA
- Discharge current 10kA
- Energy capability 5,1kJ/kV
- Rated short circuit 40kA
- 2 hole NEMA line terminal
- Grounding connector for cable 10 to 120mm2
- Name plate in stainless steel
- Corona ring for 120kV and 144kV voltage arresters
- Available mounting option on pole at bracket "L" for 9kV to 42kV voltages

General

Catalog Number ZYP2710 Residual Voltage (1 ? (max.)) 72



*Representative Image

Residual Voltage (8 x 20? 73.8

(max.))

Dimensions

Height 318 mm

Electrical Ratings

Creep and Leakage Distance 730 mm

Operating Voltage 22000 VAC

Voltage Rating 27 kV

Product Assets

Catalogs - Para-raios Estação modelo ZYP 9kV a 144kV Literature - Application Guide: Metal-oxide Surge Arresters for use on AC systems Specifications - ZYP2710

