

## SDC™ Composite Bushing - 34.5kV

By Electro Composites  
Catalog # 200-004-W-642-00

SDC™ 34.5kV-400 A Wall/Floor Condenser Bushing, Solid-Dielectric-Capacitor Type, Rated per IEEE C57.19.01, Bottom Connected for Air-to-Air Applications, 2" Ground Shield Length, 47.6" Min. Creepage Length



\*Representative Image

### Features

- SDC™ - Solid Dielectric Capacitance Graded Composite Construction
- EC-APG-02 Cycloaliphatic Epoxy Compound for Optimal Performance
- Meets IEEE C57.19.01 Electrical and Mechanical Requirements
- Can be mounted vertically or horizontally

### Application

Wall/Floor

### General

Bottom Terminal Type	1x Blade with 2x 0.50 Dia Holes
Color	Gray
Immersion Type - Above Flange	Air
Immersion Type - Below Flange	Air
Material - Flange	Epoxy
Material - Insulation	APG-02 - Cycloaliphatic Epoxy
Mounting Position	Vertical to Horizontal
Number of Bolt Holes - Bottom Terminal	2
Number of Bolt Holes - Top Terminal	2
Number of Flange Mounting Holes	4
Plating - Bottom Terminal	None
Test Tap	No
Top Terminal Plating	None
Top Terminal Type	1x Blade with 2x 0.50 Dia Hole
Type	Condenser Bushings

### Dimensions

Above Flange Length	26.19 in
Below Flange Length	22.06 in
Diameter - Above Flange Maximum	8.64 in
Diameter - Below Flange Maximum D <gt;/> 1"	4.49 in
Diameter - Below Flange Maximum P	4.49 in
Diameter - Live Part Bottom	1.25 in
Diameter - Live Part Top	2.75 in
Effective Length - Bottom Terminal	3.25 in
Effective Length - Top Terminal	3.25 in
Flange Mounting Hole Bolt Circle	6.50 in
Flange Mounting Hole Diameter	1/2-13
Flange Outside Diameter	8.64 in
Length	48.25 in
Length - Ground Shield	2.00 in
Length - Insulation Above Flange	21.30 in
Length - Insulation Below Flange	16.06 in
Length - Live Part Bottom	4.00 in
Length - Live Part Top	4.60 in
Length - Minimum Oil Immersion Level	NA
Sealing Surface Inside Diameter	4.49 in
Sealing Surface Outside Diameter	7.55 in
Weight	61 lb

### Electrical Ratings

BIL	200 kV
Current Rating	400 A
Minimum Creepage	47.60 in
Minimum Creepage - Inside	28.40 in
Minimum Strike	23.80 in
Minimum Strike - Inside	17.50 in
Withstand Voltage - 60 Hz Dry	80 kV
kV Class	34.5 kV

## Certifications and Compliance

Industry Standard(s)

IEEE C57.19.01

## Product Assets

[Installation Manuals - SDC™ Bushing General Handling and Maintenance Guide - Electro Composites](#)  
[Literature - Apparatus Bushings Selection Guide \(TD02026E\)](#)  
[Literature - SDC™ GSU Bushings - Electro Composites \(SF02018E\)](#)  
[Literature - SDC™ HV Generator Bushings - Electro Composites \(SF02019E\)](#)  
[Literature - SDC™ HV Bushings - Electro Composites \(SF02017E\)](#)  
[Literature - EC SDC Solid Dielectric Bushings v3](#)  
[Literature - FRENCH V2 - EC Generation Bushings](#)  
[Literature - FRENCH V2 - EC GSU Bushings](#)  
[Literature - How an SDC Bushing Test Tap is Constructed](#)  
[Sales Drawings - 642-00\\_6917-6647](#)  
[Video - ElectroComposites Factory Tour: St. Jerome \(VI00124E\)](#)



A proud member of the Hubbell Family.

©2024 Hubbell Incorporated. All rights reserved.  
EC-200-004-W-642-00-SPEC-EN | REV 1/2024