

HUBBELL

Power Systems

SDC™ Composite Bushing - 69kV

By Electro Composites
 Catalog # [350-012-W-635-01](#)

SDC™ 69kV-1200 A Wall/Floor Condenser Bushing, Solid-Dielectric-Capacitor Type, Rated per IEEE C57.19.01, Bottom Connected for Air-to-Air Applications, 3" Ground Shield Length, 53.4" Min. Creepage Length



*Representative Image

Features

- SDC™ - Solid Dielectric Capacitance Graded Composite Construction
- EC-APG-02 Cycloaliphatic Epoxy Compound for Optimal Performance
- No oil, paper or porcelain
- Can be mounted vertically or horizontally
- Meets IEEE C57.19.01 Electrical and Mechanical Requirements

General

Application	Wall/Floor
Bottom Terminal Type	1.500 Dia Smooth
Color	Gray
Immersion Type - Above Flange	Air
Immersion Type - Below Flange	Air
Material - Flange	Aluminum
Material - Insulation	APG-02 - Cycloaliphatic Epoxy
Mounting Position	Vertical to Horizontal
Number of Flange Mounting Holes	6
Plating - Bottom Terminal	None
Test Tap	Yes
Top Terminal Plating	None
Top Terminal Type	1.500 Dia Smooth
Type	SDC - Solid Dielectric Capacitor

Dimensions

Above Flange Length	29.05 in
Below Flange Length	29.35 in
Diameter - Above Flange Maximum	7.75 in
Diameter - Below Flange Maximum D <gt;/> 1"	7.75 in
Diameter - Below Flange Maximum P	7.75 in
Diameter - Live Part Bottom	4.50 in
Diameter - Live Part Top	4.50 in
Dimensions	58.40 in x 12.00 in x 12.00 in
Effective Length - Bottom Terminal	3.00 in
Effective Length - Top Terminal	2.50 in
Flange Mounting Hole Bolt Circle	10.75 in
Flange Mounting Hole Diameter	0.63 in
Flange Outside Diameter	12 in
Height	12 in
Length	58.4 in
Length - Ground Shield	3.00 in
Length - Insulation Above Flange	21.60 in
Length - Insulation Below Flange	22.55 in
Length - Live Part Bottom	3.80 in
Length - Live Part Top	3.30 in
Length - Minimum Oil Immersion Level	NA
Sealing Surface Inside Diameter	7.8 in
Sealing Surface Outside Diameter	10.12 in
Stud Inside Diameter	0.88 in
Weight	159 lb
Width	12 in

Electrical Ratings

BIL	350 kV
Current Rating	1200 A
Minimum Creepage	53.4 in
Minimum Creepage - Inside	54.00 in
Minimum Strike	22.9 in
Minimum Strike - Inside	18.60 in
Withstand Voltage - 60 Hz Dry	160 kV
kV Class	69 kV

Certifications And Compliance

Industry Standard(s) IEEE C57.19.01

Product Assets

[Installation Manuals - SDC™ Bushing General Handling and](#)

[Maintenance Guide - Electro Composites](#)

[Sales Drawings - 635-01_6491-8315](#)

[Video - ElectroComposites Factory Tour: St. Jerome](#)



A Hubbell brand

©2024 Hubbell Incorporated. All rights reserved
EC-350012W63501-SPEC-EN | REV 6/2024