HUBBELL Power Systems

Compression Deadend, Uni-Grip®(One Die), Full Tension

By FARGO Catalog # A101023NT



•

•

•

General

Туре

Bolt Installation Torque (Recommended)	O ft-lbs
Compression Method	Uni-Grip (single die system)
Die Size	10CD
Material	Aluminum; Steel
Material - Body	Seamless Extruded Aluminum Alloy
Material - Clevis	Galvanized Forged Steel
Material - Hardware	Aluminum Alloy
Material - Pin (Cotter)	#304 Stainless Steel
Number of Bolt Holes	2
Number of Pad Holes	0
Press Minimum	60 to
Product Category	Adjustable Clevis
Style	Uni-Grip, Double Tongue,
	Adjustable Clevis
Tension Range	0 lb
Terminal Option	No

Compression

Dimensions

Actual Clamp Strand Diameter	0 in
Range	
Adjustment Step	0 in
Angle - Pad	0 °
Bolt Diameter	0.75 in
Clamping - Maximum	0 in
Clamping - Minimum	0 in
Diameter - Clamping Hardware	0 in
Diameter - Clevis Pin	0 in
Diameter - Eye Hole	0 in
Diameter - Inside	0 in
Diameter - Outside	0.879 in
Diameter - Pad Bolt	0 in
Length - Pin	0 in
Length Before Compression	21 in
Maximum Adjustment	2.8 in
Messenger Diameter Range	0 - 0
Take Up	0 in
Thickness - Pad	0 in
Total Adjustment	0 in
Width - Pad	2 in

Electrical Ratings

Voltage Application Standard

Conductor Related

Clamping Range	0-0
Conductor Compatibility	ACSR-Osprey-556.5-18/1
Conductor Diameter (Main) -	0 in
Maximum	
Conductor Diameter (Main) -	0 in
Minimum	
Conductor Diameter (Main)	0 - 0
Range	
Messenger Diameter -	0 in
Maximum	
Messenger Diameter - Minimum	O in

Product Assets

Catalogs - Transmission Connectors Catalog - Full

