

Compression Deadend

By FARGO
Catalog # C101414

Compression Deadend, Uni-Grip, Double Tongue, Adjustable Clevis, for AAC, Dia. Range 1.236 - 1.33, With Terminals



*Representative Image

Features

- For use with AAC code names: Hawthorn, Narcissus
- Full tension Deadend assembly
- Steel Adjustable Clevis threaded stub factory compressed in deadend
- Prefilled with joint compound
- Jumper Terminal & Mounting Hardware included

General

Compression Method	Uni-Grip (single die system)
Die Size	14CD
EU RoHS Indicator	No
Material	Aluminum; Steel
Material - Body	Seamless Extruded Aluminum Alloy
Material - Clevis	Galvanized Forged Steel
Material - Hardware	Aluminum Alloy
Material - Pin (Cotter)	#304 Stainless Steel
Material - Terminal	Seamless Extruded Aluminum Alloy
Number of Bolt Holes	4
Press Minimum	60 to
Product Category	Adjustable Clevis
Style	Uni-Grip, Double Tongue, Adjustable Clevis
Type	Adjustable Clevis
UPC	096359466987

Dimensions

Bolt Diameter	1.000 in
Diameter - Clamping Hardware	0 in
Length Before Compression	23.8 in
Maximum Adjustment	3.5 in
Messenger Diameter Range	0 - 0
Width - Pad	3 in

Electrical Ratings

Voltage Application	EHV; Standard
---------------------	---------------

Conductor Related

Clamping Range	0 - 0
Conductor Compatibility	AAC-Hawthorn-1192.5-61; AAC-Narcissus-1272-61
Conductor Diameter (Main) Range	0 - 0
Conductor Diameter - Maximum	1.33 in
Conductor Diameter - Minimum	1.236 in
Conductor Diameter Range	1.236 - 1.33

Product Assets

[Catalogs - Transmission Connectors Catalog - Full \(CA05063E\)](#)