HUBBELL
Power Systems

# Formed Wire Distribution Grip Deadend #1

By FARGO
Catalog # DGFW4543

*Representative Image

Formed Wire Distribution Grip Deadend for #1 ACSR, AAC, AAAC, Compacted ACSR and AWAC® (#1 6/1, #2 5/2)

## Features

- For deadending bare or plastic jacketed conductor on primaries, secondaries, and substation feeder applications
- For use on ACSR, AAC, AAAC, Compacted ACSR and AWAC®
- Aluminum clad steel construction
- DGFW deadends will hold a minimum of 60% of the cable (RBS) rated breaking strength.

## Application

Deadend for Distribution Feeder

## General

| | |
|---|---|
| Catalog Number | DGFW4543 |
| Color Code | Green |
| Material | Aluminum Clad Steel |
| Product Category | Overhead |
| Type | Formed Wire |
| UPC | 096359641544 |

## Dimensions

| | |
|---|---|
| Length | 26 in |
| Weight | 0.544 lb |

## Conductor Related

| | |
|---|---|
| Conductor Diameter - Maximum | 0.364 |
| Conductor Diameter - Minimum | 0.326 |
| Conductor Diameter Range | 0.326 - 0.364 |
| Conductor Type | ACSR, AAC, AAAC, Compacted ACSR and AWAC® |

## Logistics

| | |
|---|---|
| Carton Quantity | 50 |
| Pallet Quantity | 1400 |

## Product Assets

Literature - Ropes Course Industry Letter (April 2021)
Sales Drawings - DGFW Formed Wire Distribution Grip
Specifications - DGFW4543



©2024 Hubbell Incorporated. All rights reserved