

**Double Sheild Wire Helical
Cushioned Suspension Clamp
Assembly**

By FARGO
Catalog # [DSWHCSAGS0500](#)



*Representative Image

The DWSHCSA is a bolted aluminum suspension clamp designed to provide enhanced conductor support and protection. The DSWHCSA combines a cast aluminum clamp assembly with helical aluminum alloy rod sets and EPDM rubber inserts. The rubber inserts are assembled directly onto the conductor and are held in place with helical rods. The clamp assembly is then bolted around the helical wrapped rubber supporting inserts to complete the install.

Features

- "The DSWHCSA clamps are used for Alumoweld® and EHS Galvanized Steel applications
- The DSWHCSA clamps are two SWHCSA clamps with one shared set of helical rods
- Double Suspension for 30° - 60° line angle application
- Slip load is 15-20% of respective conductor RBS (Contact Hubbell for more Information)
- Application O.D. = (Helical Rod O.D. X 2) + Conductor O.D
- DSWHCSA is supplied with BNK and does not include fittings"

General

Catalog Number	DSWHCSAGS0500
Type	Shield Wire

Logistics

Pallet Quantity	16
-----------------	----

Product Assets

[Literature - Ropes Course Industry Letter \(April 2021\)](#)
[Literature - Suspenion Clamps DSWHCSA](#)
[Sales Drawings - CC-27006](#)
[Specifications - DSWHCSAGS0500](#)