

## Automatic Splice, Bi-Metal (Copper to Aluminum)

By FARGO  
Catalog # [GL41118](#)



Automatic Splice, Bimetallic, 397.5 AAC, 394.5 AAAC, 336.4 (18/1) ACSR to 3/0 Solid Copper & 2/0 Stranded Copper

\*Representative Image

### Features

- Provide a mechanical and electrical connection of copper to ACSR, aluminum, or aluminum alloy conductors
- Individually bagged to seal out dirt before use.
- Factory loaded inhibitor to ensure long term corrosion free performance.

### General

Color Code	None
EU RoHS Indicator	Contact Manufacturer
Material	Aluminum Alloy
UPC	096359482994

### Dimensions

Weight	1.568 lb
--------	----------

### Conductor Related

Conductor Compatibility	ACSR-Merlin-336.4-18/1
-------------------------	------------------------

### Certifications and Compliance

UL Listed	No
-----------	----

### Product Assets

[Catalogs - Communication Connectors - Deadends and Splices](#)  
[Catalogs - Distribution Connectors \(CA05127E\)](#)  
[Literature - Quick Reference Guide: Splices for Overhead Connections \(LEEDS-HPS-SPLICES-QUICK-REFERENCE-GUIDE-SF-EN-2023\)](#)  
[Video - Hubbell Power Systems Automatic Splice Installation \(VI0548E\)](#)