HUBBELL Power Systems

Compression Deadend

By FARGO Catalog # SEDA1813SSAC

Full-tension deadend assemblies for ACSR conductors consist of an aluminum deadend body, steel deadend eye, 15° jumper terminal and terminal mounting hardware. Terminal and tongue have NEMA hole spacing.



Features

- For use with ACSS code name Hen
- Must use High-Temp compount HTJC16
- Full tension Deadend assembly
- Joint Compond purchased separately
- Jumper Terminal & Mounting Hardware included

General

Aluminum Die	24AH
Bolt Installation Torque	O ft-lbs
(Recommended)	
Catalog Number	SEDA1813SSAC
Compression Method	Conventional (2 die system)
EU RoHS Indicator	No
Inhibitor Loaded	No
Material	Aluminum; Steel
Material - Body	Seamless Extruded Aluminum
	Alloy
Material - Eye	Galvanized Forged Steel
Material - Hardware	Aluminum Alloy
Material - Terminal	Seamless Extruded Aluminum
	Alloy
Number of Bolt Holes	2
Number of Pad Holes	0
Press Minimum	60 to
Product Category	Assemblies
Style	Conventional 2-Die, Single
	Tongue
Tension Range	0 lb
Туре	Compression
UPC	096359465928

Dimensions

Actual Clamp Strand Diameter	0 in
Range	
Adjustment Step	0 in
Angle - Pad	0 °
Clamping - Maximum	0 in
Clamping - Minimum	0 in
Diameter - Clamping Hardware	0 in
Diameter - Clevis Pin	0 in
Diameter - Eye Hole	0 in
Diameter - Inside	0 in
Diameter - Outside	0.883 in
Diameter - Pad Bolt	0 in
Length - Pin	0 in
Length Before Compression	18.6 in
Messenger Diameter Range	0 - 0
Take Up	0 in
Thickness - Pad	0 in
Total Adjustment	0 in
Width - Pad	2.5 in

Electrical Ratings

Voltage Application Standard

Conductor Related

Clamping Range	0-0
Conductor Compatibility	ACSS-Hen-477-30/7
Conductor Diameter (Main) -	0 in
Maximum	
Conductor Diameter (Main) -	0 in
Minimum	
Conductor Diameter (Main)	0 - 0
Range	
Messenger Diameter -	0 in
Maximum	
Messenger Diameter - Minimum	0 in

Product Assets

Catalogs - Transmission Connectors Catalog - Full Video - Installation of Hubbell's Conventional Compression Deadends for ACSR and ACSS Conductors

