

Compression Deadend

By FARGO Catalog # SEDA2512SSACNT

Compression Deadend, Conventional 2-Die, Single Tongue, for ACSS 636.0 kcmil 36/1, Without Terminal



*Representative Image

Features

- For use with ACSS code name Aug
- Must use High-Temp compount HTJC16
- Full tension Deadend assembly
- Joint Compond purchased separately
- "NT" suffix eliminates Jumper Terminal & Mounting Hardware

General

| Aluminum Die | 27AH |
|----------------------|--------------------------------------|
| Compression Method | Conventional (2 die system) |
| Inhibitor Loaded | No |
| Material | Aluminum; Steel |
| Material - Body | Seamless Extruded Aluminum Alloy |
| Material - Eye | Galvanized Forged Steel |
| Material - Hardware | Aluminum Alloy |
| Number of Bolt Holes | 4 |
| Press Minimum | 60 to |
| Product Category | Assemblies |
| Style | Conventional 2-Die, Single Tongue |

Dimensions

| O in |
|----------|
| 0.93 in |
| 19.14 in |
| 0 - 0 |
| 3 in |
| |

Electrical Ratings

| Voltage Application | Standard |
|---------------------|----------|
|---------------------|----------|

Conductor Related

| Clamping Range | 0-0 |
|---------------------------|-------|
| Conductor Diameter (Main) | 0 - 0 |
| Range | |

Product Assets

Catalogs - Transmission Connectors Catalog - Full (CA05063E)

Video - Installation of Hubbell's Conventional Compression Deadends for ACSR and ACSS Conductors(VI05053E0720)

Terminal Option

Туре

Compression