HUBBELL Power Systems

Compression Deadend

By FARGO Catalog # SEDA3309SSAC

Full-tension deadend assemblies for ACSR conductors consist of an aluminum deadend body, steel deadend eye, 15° jumper terminal and terminal mounting hardware. Terminal and tongue have NEMA hole spacing.



*Representative Image

Features

For use with ACSS code name Drake

• Must use High-Temp compount HTJC16

· Full tension Deadend assembly

Joint Compond purchased separately

• Jumper Terminal & Mounting Hardware included

General

Aluminum Die 30AH **Bolt Installation Torque** 0 ft-lbs

(Recommended)

Catalog Number SEDA3309SSAC

Compression Method Conventional (2 die system)

Inhibitor Loaded Nο

Material Aluminum; Steel

Seamless Extruded Aluminum Material - Body

Alloy

Material - Eye Galvanized Forged Steel

Material - Hardware Aluminum Allov

Material - Terminal Seamless Extruded Aluminum

Alloy

Number of Bolt Holes 4 Number of Pad Holes 0 Press Minimum 60 to **Product Category** Assemblies

Conventional 2-Die, Single Style

Tongue

0 in

0 lb Tension Range

Type Compression **UPC** 096359384199

Dimensions

Diameter - Inside

Actual Clamp Strand Diameter 0 in

Range

Adjustment Step 0 in 0 ° Angle - Pad 0 in Clamping - Maximum Clamping - Minimum 0 in Diameter - Clamping Hardware 0 in Diameter - Clevis Pin 0 in Diameter - Eye Hole 0 in Diameter - Outside 1.108 in Diameter - Pad Bolt 0 in

Dimensions 20.13 in x 27.33 in x 3 in

3 in

Height Length 20.13 in Length - Pin 0 in Length Before Compression 21.8 in Messenger Diameter Range 0 - 0 Take Up 0 in Thickness - Pad 0 in Total Adjustment 0 in Weight 10 lb Width 27.33 in Width - Pad 3 in

Electrical Ratings

Voltage Application EHV; Standard

Conductor Related

 \cap - \cap Clamping Range

Conductor Compatibility ACSS-Drake-795-26/7

Conductor Diameter (Main) -0 in

Maximum

Conductor Diameter (Main) -0 in

Minimum

Conductor Diameter (Main) 0 - 0

Range

Messenger Diameter -0 in

Maximum

Messenger Diameter - Minimum 0 in

Certifications And Compliance

Buy America(n) Qualified TAA Compliant (All status valid

till December 2024)

Product Assets

Catalogs - Transmission Connectors Catalog - Full

Sales Drawings - SEDA3309SSAC Specifications - SEDA3309SSAC

Video - Installation of Hubbell's Conventional Compression

Deadends for ACSR and ACSS Conductors

