HUBBELL
Power Systems

Compression Splice Conventional (Two Die) Full Tension ACSR Conductor

By FARGO
Catalog # TJA6028

*Representative Image

Splice assemblies for ACSR conductors consist of an aluminum splice body and steel sleeve. Material: body - seamless extruded aluminum tube, steel sleeve - plated steel.

Features

- For use with ACSR code name Chucker
- Full tension Splice assembly
- Joint Compound purchased separately

General

Aluminum Die	42AH
Catalog Number	TJA6028
Compression Method	Conventional (2 die system)
Inhibitor Loaded	No
Material	Aluminum; Steel
Press Minimum	100 to
Tension Range	0 lb
UPC	096359568315

Dimensions

Adjustment Step	0 in
Assembly Rating (Ultimate)	0 lb
Diameter - Outside	1.602 in
Insulator / Conductor Hole Spacing	0 in
Length Before Compression	35.7 in
Messenger Diameter Range	0 - 0

Electrical Ratings

Voltage Application	EHV; Standard

Conductor Related

Conductor Compatibility	ACSR-Chukar-1780-84/19
Conductor Diameter (Main) - Maximum	0 in
Conductor Diameter (Main) - Minimum	0 in
Conductor Diameter (Main) Range	0 - 0
Conductor Type	ACSR
Messenger Diameter - Maximum	0 in
Messenger Diameter - Minimum	0 in

Certifications And Compliance

UL Listed	No

Product Assets

Catalogs - Transmission Connectors Catalog - Full Specifications - TJA6028

©2024 Hubbell Incorporated. All rights reserved