

55-4E-2DP-WL-111 Series 55 Limit Switch DPDT

By Gleason Reel Catalog # 55-4E-2DP-WL-111

Series 55 Limit Switch DPDT



Features

- Easy, precision timing adjustment using standard screwdriver and provided tool
- Industrial grade oil-impregnated bronze bearings
- Switch terminal screws for quick wiring
- Operating temperature range is -20F to +150F
- Humidity up to 90% is acceptable
- Ambient pressure of -0.5 to +2.0 psig is acceptable (where 0 psig equals 14.7 psi atmospheric)

General

Product Category Series Limit Switches 55

Dimensions

Circuits Normally Open2Maximum Shaft Turns To Trip35Contacts1.5Minimum Shaft Turns To Trip1.5Contacts7.5Over Travel Shaft Turns7.5Reset Shaft Turns0.75	Circuits Normally Closed	2
Contacts Minimum Shaft Turns To Trip 1.5 Contacts Over Travel Shaft Turns 7.5	Circuits Normally Open	2
Contacts Over Travel Shaft Turns 7.5		35
	•	1.5
Reset Shaft Turns 0.7	Over Travel Shaft Turns	7.5
	Reset Shaft Turns	0.75

Certifications and Compliance

Nema Rating 4

Product Assets

Brochures - Pre-Engineered Products - Reels, Cable Track and Festoons, Controls, Automation Components Brochures - GLEASON_Series55_BROCHURE Engineering Drawing - Series 55 Rotary Limit Switch DXF Engineering Drawing - Series 55 Rotary Limit Switch DWG Installation Manuals - Limit Switch-Series 55 Adjustment and Maintenance Instruction 630535 Technical Solutions - GRD-55-4E-2DP-WL-111-SPEC-EN