GAI-TRONICS

Clean Phone® VoIP Telephone, 14 Button, Surface-Mount, CE certified RoHS compliant

By GAI-Tronics Catalog # 116-02-0418-01W

The Clean Phone® telephone offers hands-free communications over an existing VoIP network for clean room environments. These telephones are intended for connection via RJ45 to a 10/100 BaseT Ethernet and operate using either PoE or an external dc power source. The Clean Phone® VoIP telephone features alarm reporting that enables system supervisors to monitor the telephone's activity and address maintenance issues immediately. The Clean Phone® telephone is also compatible with GAI-TRONICS' TMA (Telephone Management Application) software for maintenance monitoring from a central location. Embedded web pages permit access to each telephone, via a browser such as Internet Explorer®, to view, monitor, and change settings within the unit.



- · Clean Rooms
- Clinical Environments
- Sterile Environments
- Sanitary Environments

General

CE Compliant CE certified RoHS compliant,

Sterile Area

Connectivity Options VoIP

Mount location Surface-Mount

Operating Temperature -20° C to +60° C

Storage Temperature Range -40° C to +70° C

Type Keypad



Certifications and Compliance

CE Compliant CE certified RoHS compliant,

Sterile Area

Product Assets

Installation Manuals - VoIP Clean Phone® Telephones (1193 Version)

