

Behavioral Health Surface-Mount Analog Telephone (Keypad)

By GAI-Tronics
Catalog # 210-001BH



GAI-Tronics Behavioral Health series of rugged telephones are designed for use in environments where conversation privacy is desired but safety is a concern. The Model 210-001BH (Keypad) is ideally suited for installation in any area requiring the Americans with Disabilities Act maximum protrusion Depth of 4 inches (corridors, hallways, passageways) or on any flat surface. The unit's rear mounting plate provides telephone line access, eliminating visibility of, or access to, cabling. Additionally, the 210-001BH is secured with security hardware to prevent vandalism.

Features

- Surface-Mount design for Indoor Use
- Standard Telephone Operation
- Braille Chrome-plated Keypad
- Brushed Stainless Steel Housing
- Front Panel Pushbutton Volume Control
- Handset with Noise-cancelling Microphone, Hearing Aid-compatible Receiver, and 12-inch Armored Cord with Anchored Lanyard
- Ringer with Loudness Control
- Dry Contact Closure Output (off-hook)
- Less than 3½-inch Depth
- UL 60950 / CSA C22.2 No. 60950
- FCC Part 68 Certified
- ADA Compliant for Corridor Installation

General

Application	Rehabilitation Centers Correctional Facilities Mental Health Facilities
Connectivity Options	Analog
Material	Enclosure Construction: 16-gauge (.060-inch) Type 304 brushed stainless steel; Braille Dial Pad: Chrome-plated zinc
Mount location	Surface-Mount
Operating Temperature	-40° F to +140° F
Type	Keypad

Dimensions

Cubic Capacity	179.85 cu.in
Depth	3.27
Height	10 in
Weight	5.5 lb
Width	5.5 in

Certifications And Compliance

Certification	UL CSA
Certified Listed	UL 60950 CSA C22.2 No. 60950
Compliance	FCC Part 68 Certified

Product Assets

- [Brochures - Rugged Telephone Brochure](#)
- [Brochures - Behavioral Health Telephones](#)
- [Installation Manuals - Analog Corridor Telephones - Model 210 Series](#)
- [Literature - Behavioral Health Surface-mount Analog Telephones](#)



A Hubbell brand

©2024 Hubbell Incorporated. All rights reserved
GTC-210001BH-SPEC-EN | REV 6/2024