



Solar/Cellular GSM Tower

By GAI-Tronics
Catalog # 234-600GSM

Free-standing tower, GSM cellular; including lens cover, solar mast, mast assembly kit, lighting kit (includes strobe), GSM & charging regulator subpanel, battery kit; 12 V dc solar power.

Features

- Architectural Bronze and Safety Blue Standard Colors
- UL Listed
- ADA Compliant
- Durable Powder-coated Epoxy Finish
- Custom Colors and Graphics Available
- Wind Speed Rated @ 140 MPH* (*Reference AASHTO LTS6 Risk Category II
- International Building Code)
- “EMERGENCY” lettering on all sides for high visibility
- Accommodates GAI-TRONICS’ flush-mount emergency telephones (sold separately)
- Includes LED Panel Light, 10-33 Vdc

General

Catalog Number	234-600GSM
Compatibility	GAI-TRONICS’ Telephones and Solar Panel Array sold separately. Model 234 Tower is not compatible with RED ALERT® surface-mount or retrofit telephones.



Finish Type	Powder-Coated Epoxy
Material	Steel
Type	Cellular Tower
Weather Rating	UL/cUL listed Outdoor Telephone Tower

Dimensions

Cubic Capacity	11400 cu.in
Depth	10 in
Height	114 in
Width	10 in

Certifications And Compliance

Certified Listed	UL/cUL
------------------	--------

Product Assets

- [Brochures - Red Alert Telephone Brochure](#)
- [Brochures - Emergency Communications Tower Applications \(Solar/Wireless/Surveillance\)](#)
- [Specifications - 234600GSM](#)
- [Video - Gai-Tronics Emergency Phones](#)