GAI-TRONICS

Indoor Rugged Telephone - Analog/SMART (Keypad)

By GAI-Tronics Catalog # 246-005

This indoor series telephone is constructed of a high-impact, non-metallic enclosure with an industrial strength, six-foot (extended) Hytrel® handset cord. SMART models include the ability to be centrally monitored for health status via our TMA software.

Features

- Telephone Line Powered
- · No External Power Needed
- Braille Metallic Keypad
- Handset with Noise-canceling Microphone and Hytrel® Coiled Cord (6-ft extended)
- · Hearing Aid Compatible Handset
- Volume Control Push Button (Front Panel)
- Non-movable Hookswitch
- Remote Programming
- Phone's Health Status Reported to Central P.C.
- Programmable Polling or Call-in Scheduling
- Dual Output Control
- Conformal Coated PCBA
- Three Number Rollover Unit Dials up to Three Different Numbers to Ensure
- FCC & IC Certified, UL60950 Listed
- TMA Compatible

Application

Indoor Use

General

| Catalog Number | 246-005 |
|----------------|---------|
| Color | Gray |

Connectivity Options Analog/SMART
Mount location Surface-Mount
Output Level Ringer 90 dBA @ 2 ft.

Signal Type Analog

Specifications UL/CSA, FCC, IC



| Type | Keypad |
|----------------|--------|
| Weather Rating | Indoor |

Dimensions

| Dimensions | 6.9 in x 8 in x 9.5 in |
|------------|------------------------|
| | |

Height 9.5 in
Length 6.9 in
Weight 4.8 lb
Width 8 in

Electrical Ratings

| Input Voltage | Phone Line |
|---------------|------------|
| Signal | Phone Line |

Certifications And Compliance

Certified Listed UL/CSA, FCC, IC

Product Assets

Brochures - Rugged Telephone Brochure

Installation Manuals - SMART Handset Telephones with Keypads

(Model 226-005, 246-005, 256-005, and 276-005)

Installation Manuals - Telephone Management Application

Installation Bulletin

Installation Manuals - Telephone Installation Safety Rules

Installation Manuals - Telephone Management Application (TMA)

User Guide

Literature - SMART Rugged Telephones - Keypad Literature - Telephone Management Application (TMA)

Specifications - 246-005

