

# Intrinsically Safe Telephone - Indoor, Analog

By GAI-Tronics  
Catalog # 262-001

Housed in durable glass-reinforced polyester for indoor applications, GAI-TRONICS' Intrinsically-Safe Telephones are the safest and most economical communication solution in hazardous environments. Consists of models 262-001 (Intrinsically Safe Telephone - Indoor) and 263-000 (Isolation Barrier)



## Features

- North American Listed for All Hazardous Groups
- cUL / UL Listed
- Replaces Explosionproof Telephones without Replacing System Cable in Most Applications
- Braille Metallic Keypad
- "Shrill"-type Penetrating Ringer
- Noise-cancelling Microphone
- Volume Control Handset
- Low Sidetone for Noisy Environments
- Switchable Power Supply - 110 VAC / 220 VAC
- Hytrel® Coil Cord for Maximum Durability
- Hearing Aid Compatible (HAC)
- Extreme operating temperature range

## General

Color	Gray
Connectivity Options	Analog
Mount location	Surface-Mount
Output Level Ringer	85 dBA @ 2 ft.
Signal Type	Analog
Weather Rating	Type 12

## Dimensions

Dimensions	6.86 in x 8.02 in x 9.52 in
Height	9.52 in
Length	6.86 in
Weight	5 lb
Width	8.02 in

## Electrical Ratings

Signal	I.S.
--------	------

## Certifications And Compliance

Certification	UL/CSA, FCC, IC
Hazardous Rating(s)	Division 1, Class I, Groups A, B, C, & D Division 1, Class II, Groups E, F, & G Division 1, Class III Division 2, Class I, Groups A, B, C, & D Division 2, Class II, Groups E, F, & G Division 2, Class III

## Product Assets

- [Brochures - Rugged Telephone Brochure](#)
- [Installation Manuals - Intrinsically-Safe Telephones \(Model 262-001 and 272-001\)](#)
- [Literature - Intrinsically Safe Telephones](#)



**A Hubbell brand**

©2024 Hubbell Incorporated. All rights reserved  
GTC-262001-SPEC-EN | REV 6/2024